



Prokuplje, Dragoljuba Rakića 7a
+381 27 321 177; +381 27 334 310
Tekući račun: 325-950080000702-77

kontakt@abmelektro.com
www.abmelektro.com
PIB: 100 415 391



RADE KONČAR KONTAKTORI I RELEI D.O.O.



Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata Y T	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI CNN, naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
20	3.0	1 0 0 1	45x48x57	0.17	CM1 01	1791
25	4.5	0 0	45x71x72,2	0.25	CNN 9 00	1811
		1 0			CNN 9 10	1845
		0 1				
25	4.5	0 0	45x71x72,2	0.25	CNN 9 004 ; CNN 9 00 22	1844
25	5.7	0 0	45x71x72,2	0.25	CNN 12 00	2011
		1 0			CNN 12 10	2048
		0 1				
25	5.7	0 0	45x71x72,2	0.25	CNN 12 004 ; CNN 12 00 22	2065
30	7.5	1 0	45x71x72,2	0.26	CNN 18 10	2315
		0 1				
40	11	0 0	45x71x72,2	0.275	CNN 25 00	3136
40	15	0 0	45x71x72,2	0.290	CNN 30 00	3504
50	15	0 0	45x80x84,6	0.355	CNN 32 00	4249
50	18.5	0 0	45x80x84,6	0.355	CNN 40 00	5199
80	22	0 0	55x120x109	0.845	CNN 50 00	7512
85	30	0 0	55x120x109	0.850	CNN 60 00	9391
85	33	0 0	70x142x123	0.900	CNN 70 00	11739
90	37	0 0	70x142x123	1.280	CNN 80 00	14251
95	45	0 0	70x142x123	1.300	CNN 90 00	15498
100	55	0 0	70x142x123	1.350	CNN 100 00	16599
	55	0 0	90x179x167	2.300	CNN 115 00	20081
	75	0 0	90x179x167	2.550	CNN 150 00	24806
		Y T			Dodaci (blokovi pomoćnih kontakata)	RSD
		0 1	45x48x38	0.04	BPO (40, 31, 22, 13, 04), prednji	950
		3 1				
		2 2				
		1 3				
		0 4				
		1 0		0.013	BP1 (1NO ili 1NC), stranični	386
		0 1				
		1 1	40x35x38	0.03	BP2 11 (1NO+1NC), prednji	580
		1 1	55x10x46	0.05	BP5 11 (1NO+1NC), stranični	805
		1 1	55x10x46	0.03	BP3 11 (1NO+1NC), stranični	443
		2 2	40x35x38	0.04	BP4 22 (2NO+2NC), prednji	724
		4 0	40x35x38	0.04	* BP4 40 (4NO+0NC), prednji	724
		2 2	40x35x38	0.04	BP2 N 11 (1NO+1NC), prednji	805
		2 2	40x35x38	0.04	BP4 N 22 (2NO+2NC), prednji	967



Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata 1 2	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI CNM, naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
115	55	2 2	100x132x142	2.29	CNM 110 22	21389
		4 4	125x132x142	2.39	CNM 110 44	23095
160	75	2 2	135x180x189	5.10	CNM 140 22	32437
		4 4	135x180x189	5.60	CNM 140 44	34795
200	90	2 2	135x180x189	5.20	CNM 170 22	36969
		4 4	162x180x189	5.70	CNM 170 44	39892
250	110	2 2	135x180x189	5.30	CNM 200 22	45372
		4 4	162x180x189	5.80	CNM 200 44	48295
300	132	2 2	160x200x226	8.40	CNM 250 22	61146
		4 4	187x200x226	8.90	CNM 250 44	64397
390	160	322	160x200x226	8.50	CNM 315 22	83076
		4 4	187x200x226	8.90	CNM 315 44	86002
400	200	2 2	160x200x226	8.50	CNM 400 22	94100
		4 4	187x200x226	8.90	CNM 400 44	97023
700	250	2 2	220x250x225	13.50	CNM 450 22	156800
800	315	2 2	220x250x225	14.00	CNM 550 22	186666
1000	400	2 2	280x307x291	26.40	CNM 700 22	216263
1100	500	2 2	280x307x291	27.80	CNM 860 22	297175
1200	580	2 2	334x490x345	51.00	CNM 1000 11	952750
		Težina(kg)	Dodatci			
			RC elementi za CNNP ; CNNB			456
		0.021	dodatci za priključke za (CNN 32 - CNN 40) za priključenje vodiča do 25mm ² , (2 komada),br.dela:601478			979
		0.14	Set od 6 štitnika (poklopca) za terminale kontaktora (CNM 75-CNM110),br.dela:603311			3257
		0.15	Set od 6 štitnika (poklopca) za terminale kontaktora (CNM 140-CNM200),br.dela:604128			3907
Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata 1 2	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI CN, naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
23	4.7	1 1	68x68x78,5	0.425	CN 10	3886
		2 0				
		0 2				
30	7.5	1 1	68x68x78,5	0.425	CN 16	4124
		2 0				
		0 2				
35	12	2 2	85x100x103	0.930	CN 25	9063
45	15	2 2	85x100x103	0.935	CN 40	11354
130	40	2 2	192x190x130	5.50	CN 80	33070
160	55	2 2	192x190x130	5.60	CN 110	39555
220	90	2 2	212x234x180	9.50	CN 170	71306
300	132	2 2	212x234x180	9.70	CN 250	100621



Nazivna nominalna struja Ie kod Un=400 V, AC 6b	Snaga konden. kod Un=400V, AC 6b	Broj pomoćnih kontakata 	Dimenzije a x b x c	Težina	Kondenzatorski kontaktori CNNK, naizmjenični napon upravljanja	Cena
(A)	(kVar)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
18	2.5	1 0	45x71x72,2	0.25	CNNK 2,5	1980
18	5	1 0	45x71x72,2	0.25	CNNK 5	2180
29	7.5	0 0	45x71x72,2	0.275	CNNK 7,5	2430
14	10	2 0	45x72,2x108	0.314	CNNK 10 20	3319
14	10	1 1	45x72,2x108	0.314	CNNK 10 11	3319
18	12.5	2 0	45x72,2x108	0.316	CNNK 12 20	3521
18	12.5	1 1	45x72,2x108	0.316	CNNK 12 11	3521
22	15	2 0	45x72,2x108	0.318	CNNK 15 20	3991
22	15	1 1	45x72,2x108	0.318	CNNK 15 11	3991
29	20	1 0	45x80x121,3	0.333	CNNK 20 10	4191
36	25	1 0	45x80x121,3	0.404	CNNK 25 E 10	5198
36	25	1 0	45x80x121,4	0.404	CNNK 25 10	5535
44	30	1 0	45x80x121,3	0.414	CNNK 30 10	6005
50	40	1 0	55x120x109	0.875	CNNK 40 10	8553
72	50	1 0	55x120x109	0.880	CNNK 50 10	9222
87	60	1 0	55x120x109	0.920	CNNK 60 10	10564
101	70	1 0	70x142x123	1.320	CNNK 65 10	15258
108	75	2 2	70x142x123	2	CNKM 75 10	16411
108	75	1 2	90x179x167	2.47	CNKM 80 12	24314
Nazivna nominalna struja Ie kod Un=230 V, AC 15/AC 14		Broj pomoćnih kontakata 	Dimenzije a x b x c	Težina	POMOĆNI KONTAKTORI, naizmjenični napon upravljanja	Cena
(A)		ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
6		4 0	45x48x56	0.17	CP0	1793
		3 1				
		2 2				
10		4 0	45x71x72,2	0.25	CNNP	1771
		3 1				
		2 2				
		1 3				
		0 4				
	sve izvedbe kao CNNP		45x71x72,2	0.27	CNNP F	2591
Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 1	Broj pomoćnih kontakata 	Dimenzije a x b x c	Težina	TERMIČKI KONTAKTORI, naizmjenični napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
65	43	2 2	45x129x113	0.59	TKN 65 00	5878
115	76	2 2	87x172x111	1.50	TKN 115 22	10631
130	85	2 2	100x158x140	2.42	TK 130 22	20377
175	115	2 2	100x158x140	2.42	TK 175 22	22298



Nazivna nominalna struja Ie kod Un=400 V, AC 2/AC3	Nazivna nominalna snaga Pn, Un=400 V, AC 2/AC3	Broj pomoćnih kontakata 1 1	Dimenzije a x b x c	Težina	Kontaktori MBCNN i MBCNM (mehanička i električna blokada)	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
6.5	2.2	0 0	83x110x56	0.41	MBCM1 00	4787
6.5	2.2	1 0	83x110x56	0.41	MBCM1 10	5178
9	4.5	0 0	100x72,2x71	0.503	MBCNN 9 00	5372
9	4.5	1 1	120x72,2x71	0.505	MBCNN 9 11	6185
12	5.7	0 0	100x72,2x71	0.503	MBCNN 12 00	5957
12	5.7	1 1	120x72,2x71	0.505	MBCNN 12 11	6773
18	7.5	0 0	100x72,2x71	0.523	MBCNN 18 00	6739
18	7.5	1 1	120x72,2x71	0.525	MBCNN 18 11	7554
25	11	1 0	100x72,2x71	0.553	MBCNN 25 10	9132
30	11	1 0	100x72,2x71	0.553	MBCNN 30 10	10207
32	15	1 0	120x80x84,6	0.713	MBCNN 32 10	12209
40	18.5	1 0	120x80x84,6	0.713	MBCNN 40 10	14456
45	22	1 0	160x140x111	2.80	MBCNN 50 10	21878
45	22	2 1	160x140x111	2.80	MBCNN 50 21	23507
60	30	1 0	160x140x111	2.82	MBCNN 60 10	27349
60	30	2 1	160x140x111	2.82	MBCNN 60 21	28977
65	33	1 0	160x140x111	2.88	MBCNN 70 10	34186
65	33	2 1	160x140x111	2.88	MBCNN 70 21	35814
75	37	1 0	200x150x102	3.78	MBCNN 80 10	41513
75	37	2 1	200x150x102	3.78	MBCNN 80 21	43141
90	45	1 0	200x150x102	3.81	MBCNN 90 10	44443
90	45	2 1	200x150x102	3.81	MBCNN 90 21	46069
110	55	2 1	200x150x102	5.78	MBCNM 110 21	48443
140	75	2 1	270x210x189	14.20	MBCNM 140 21	50181
170	90	2 1	270x210x189	14.40	MBCNM 170 21	117380
200	105	2 1	270x210x189	14.60	MBCNM 200 21	144059
250	132	2 1	310x235x226	23.00	MBCNM 250 21	200846
315	160	2 1	310x235x226	23.20	MBCNM 315 21	263064
400	200	2 1	310x235x226	23.40	MBCNM 400 21	450661
Dodatci						
				0.003	MB2, mehanička blokada za CNN9-CNN40	1156
					MB3, mehanička blokada za CNN50-CNN90	5046
Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	Bežumni kontaktori CNB jednosmerni napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 24, 110, 220 DC	RSD
10	4.5	4 0	45x90x129	0.60	CNNPB	3521
		3 1				
		2 2			CNNPB F	3995
		1 3				
		0 4				
25	4.5	0 0			CNNB 9	3589
25	5.7	0 0			CNNB 12	3856
30	7.5	0 0			CNNB 18	4326
40	11	0 0			CNNB 25	4610
	15	0 0			CNNB 30	5344



Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI jednosmerni napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 24, 110, 220 DC	RSD
16		4 0	45x75x85	0.37	CNNP 40 EG	3380
25	4.5	1 0	50x71x72,2	0.25	CNN 9 10	2654
25	5.7	1 0	50x71x72,2	0.25	CNN 12 10	2870
30	7.5	1 0	50x71x72,2	0.26	CNN 18 10	3151
40	11	1 0	50x71x72,2	0.275	CNN 25 10	3734
40	15	1 0	50x71x72,2	0.290	CNN 30 10	4088
50	15	1 0	50x80x84,6	0.36	CNN 32 10	4749
50	18.5	1 0	50x80x84,6	0.36	CNN 40 10	5775
85	22	1 0	60x120x109	0.85	CNN 50 10	8016
85	30	1 0	60x120x109	0.85	CNN 60 10	9828
90	33	1 0	75x142x123	0.90	CNN 70 10	12072
95	37	1 0	75x142x123	1.28	CNN 80 10	15665
105	45	1 0	75x142x123	1.30	CNN 90 10	17828
105	50	1 0	75x142x123	1.350	CNN 100 10	19008
250	90	2 1	135x180x189	5.20	CNM 170 21 (12)	42557
		4 3	162x180x189	5.70	CNM 170 43 (34)	45922
250	105	2 1	135x180x189	5.30	CNM 200 21 (12)	52245
		4 3	162x180x189	5.80	CNM 200 43 (34)	55596
350	132	2 1	160x200x226	8.40	CNM 250 21 (12)	72822
		4 3	187x200x226	8.90	CNM 250 43 (34)	76194
390	160	2 1	160x200x226	8.50	CNM 315 21 (12)	95634
		4 3	187x200x226	8.90	CNM 315 43 (34)	98998
450	200	2 1	160x200x226	8.50	CNM 400 21 (12)	108324
		4 3	187x200x226	8.90	CNM 400 43 (34)	111691

REZERVNI DELOVI ZA KONTAKTORE					
Cena (RSD)					
Tip	Glavni kontakti komplet	Jedan blok pomoćnih kontakata	KALEM naizmenični napon upravljanja	KALEM jednosmerni napon	Lučna komora
CNM 75	9140	842	5060	5565	3780
CNM 90	11097	842	5060	5565	3780
CNM 110	12277	842	5060	5565	3780
CNM 140	16019	1350	8397	9242	9612
CNM 170	17909	1350	8397	9242	9612
CNM 200	24856	1350	8397	9242	9612
CNM 250	33253	1350	16189	17807	19292
CNM 315	46254	1350	16189	17807	19292
CNM 400	55075	1350	16189	17807	19292
CN 63	7800		6386	7023	
CN 80	11534		9083	9990	
CN 110	13962		9083	9990	
CN 170	25043		17537	19292	
CN 250	35918		17537	19292	
TK 115	7622	1652	2867		
TK 130	10962	1652	5060		3761
TK 175	14739	1652	5060		3761
CM1			1304		
CNN 9,12,18,25			1301		
CNN 32-40			1369		
CNN 50-70			1990		
CNN 80-100			2770		
- Kod izvedbi "pojačanih" kompleta glavnih kontakata, gore navedene cene se povećavaju za 30%					
- Cene kalema se odnose samo na standardne napone upravljanja					
- Za nestandardne napone cena je 10% veća					